



## A 2384 specification solar panel

ZERO LID (Light Induced Degradation) N-type solar cell has no LID naturally which can increase power generation.

Dual-sided power generation gain increases with backside exposure to light, significantly reducing LCOE. Better light trapping and current collection to improve module power output and reliability. ...

The panel also includes an IP68 rated junction box, ensuring superior water and dust resistance. Measuring 2384 x 1303 x 33mm, it delivers an impressive efficiency of 22.5%.

**EXCELLENT PERFORMANCE OF PID RESISTANCE:** The performance of PID resistance (Potential Induced Degradation) passed the standard of TUV Nord.

BiHiKu7 Bifacial High Power Dual Cell PERC Module CS7N: 2384 x 1303 x 33 mm Front side power range: 640~670 W CS7L: 2172 x 1303 x 33 mm Front side power range: 580~610 W Wafer size 210 ...

Solar panels ASTRO 6 Semi 650W~665W Power range: 650W~665W Max. system voltage: 1500 VDC Dimension: 2384 x 1303 x 35 mm Frame thickness: 35 mm Glass thickness: 3.2 mm Cable ...

This series module features TOPCon 132 cells, with a maximum power output of 720W and an impressive efficiency rate of up to 23.2%. These modules exhibit minimal degradation and a low ...

Mountain series Double Glass BiFacial N-Type TOPCon Solar Module 700~725 Watt Model: UL -\*\*\* M-132DGN Maximum Efficiency: 23.34% Cutting Free Technology

The panel measures 2384 x 1303 x 33mm and weighs 37.5 kg, making it an ideal choice for both residential and commercial solar energy systems. The N-type technology with Tunnel Oxide ...

DISCOVER the Range PANELS | JINKO SOLAR | CHOOSE the Most Suitable Model for Your Needs | REQUEST Your Personalized Quote



# A 2384 specification solar panel

Web: <https://www.falconengineering.co.za>

